imageRUNNER 2520/i, 2525/i, 2530/i, 2535/i, 2545/i.

Compact workgroup productivity.

you can

Be more productive and reduce costs with the compact imageRUNNER 2500 series. Ideal for busy, small and medium workgroups, this versatile range provides for everyday black-and-white printing, copying, colour scanning and advanced send direct to email and network folder. With a variety of speeds up to 45ppm, excellent responsiveness and energy efficiency these devices will save you time, money and energy.

- **A range of speeds from 20 to 45ppm / cpm, A3 black-and-white**
- **Up to 2,300 sheet paper capacity**
- **Send direct to email and network folder**
- **5.7inch / 14.47cm touch screen display**
- **Class-leading energy efficiency**
- **Compact design**

Productivity and efficiency.

- Easy-to-use touch-screen display saves time and enables users to do more
- Fast everyday black-and-white printing up to 45ppm to meet the demands of busy, small-to-medium-sized workgroups
- Highly responsive – rapid recovery from sleep mode and 3.9 seconds first copy out time*
- Send in colour to a network folder or email in a variety of formats**. Save time by automatic resolution of email addresses
- Fewer interruptions with up to 2,300 sheet paper capacity
- Scan directly to USB memory key**

Compact design.

- Space-saving design to fit busy offices
- Optional inner staple and collate finisher

Environmental.

- Exceptional energy efficiency – as little as 1.5 watts power consumption in sleep mode, saves energy and cost
- Save paper – automatic double-sided output

Cost-effective.

- Low cost of ownership
- Enhanced productivity and class-leading energy efficiency maximises value
- Department ID Management helps monitor and control printing costs

Connectivity and management.

- Network interface with Remote User Interface as standard
- PCL** and optional PostScript Level 3 emulation support
- Remotely manage and monitor with iW Management Console (iWMC)
- Compatible with Canon's e-Maintenance tool – remote diagnostics, automated meter readings and consumables monitoring capability

* imageRUNNER 2535/i, 2545/i models
** Standard on i models, optional on non i models

imageRUNNER

Canon

Specifications: imageRUNNER 2500 Series

Type		Desktop or Free-standing (Reader-Printer Combined)
Maximum Original Size		A3
Copy Sizes	Cassette 1, 3, 4	A3, A4, A4R, A5R Custom size: 139.7 to 297mm x 182 to 432mm
	Cassette 2	A3, A4, A4R, A5R, Envelope (with optional Envelope Feeder Attachment-D1)
	Stack Bypass	A3, A4, A4R, A5R, Envelopes
	Custom Size	99 to 297mm x 148 to 432mm
Resolution	Reading	600dpi x 600dpi
	Copying	600dpi x 600dpi
	Printing	600dpi x 600dpi, 1200dpi x 1200dpi (UFRII-LT only)
	Number of Tones	256 Gradations
COPY/PRINT SPEED	A4	imageRUNNER 2545i / 2545: 45ppm (BW) imageRUNNER 2535i / 2535: 35ppm (BW) imageRUNNER 2530i / 2530: 30ppm (BW) imageRUNNER 2525i / 2525: 25ppm (BW) imageRUNNER 2520i / 2520: 20ppm (BW)
	A3	imageRUNNER 2545i / 2545: 22ppm (BW) imageRUNNER 2535i / 2535: 22ppm (BW) imageRUNNER 2530i / 2530: 15ppm (BW) imageRUNNER 2525i / 2525: 15ppm (BW) imageRUNNER 2520i / 2520: 15ppm (BW)
Magnification	Zoom	25-400%; Fixed: 25%, 50%, 70%, 100%, 141%, 200%, 400%
First Copy Time	Black-and-White	3.9 sec (45 / 35ppm model), 5.4 sec (30 / 25ppm model), 6.4 sec (20ppm model)
Warm-Up Time		30 seconds
Multiple Copies/Prints	Duplexing	1 to 999 sheets
Duplexing		Standard
Paper Weight	Cassette	64 to 90g/m²; Stack Bypass: 64 to 128g/m²; Duplex: 64 to 80g/m²
Paper Capacity	Cassette 1	550 sheets (80g/m²), (250 sheets for the imageRUNNER 2520i / 2520)
	Cassette 2	550 sheets for imageRUNNER 2525/i, 2530/i, 2535/i, 2545/i 50 envelopes (with optional Envelope Feeder Attachment-D1)
	Stack Bypass	100 sheets (A4, A4R, A5; 80g/m²), 50 sheets (A3; 80g/m²)
	Optional	550 sheets x 2 cassettes (80g/m²) 550 sheets x 1 cassette for imageRUNNER 2520 / 2520i only
	Paper Deck	None
	Total Capacity	2,300 sheets, (2,000 sheets for the imageRUNNER 2520i / 2520)
CPU		Canon Custom Processor, 400MHz
Memory		512MB (imageRUNNER 2500 i models), 256MB (imageRUNNER 2500 non i models)
Hard Disk Drive		None
Interface		Ethernet (100Base-TX / 10Base-T), USB Host I / F 2.0 x 1port, USB Device 1.0 x 1port
Power Supply		220-240V AC, 50/60Hz, 4.2A (45 / 35ppm model), 220-240V AC, 50/60Hz, 3.3A (30 / 25 / 20ppm model)
Max. Power Consumption		1.827kW (45 / 35ppm model), 1.345kW (30 / 25ppm), 1.542kW (20ppm model)
Dimensions (W x D x H)		imageRUNNER 2545i / 2545 / 2535i / 2535 565 x 680 x 806mm (with the platen cover), 565 x 689 x 907mm (with the DADF) imageRUNNER 2530i / 2530 / 2525i / 2525 565 x 680 x 806mm (with the platen cover), 565 x 689 x 896mm (with the DADF) imageRUNNER 2520i / 2520 565 x 680 x 681mm (with the platen cover), 565 x 689 x 771mm (with the DADF)
Weight		imageRUNNER 2545i / 253Si: Approx. 78.4kg, imageRUNNER 2545 / 2535: Approx. 70.5kg imageRUNNER 2530i / 2525i: Approx. 77.5kg, imageRUNNER 2530 / 2525: Approx. 68.0kg imageRUNNER 2520i: Approx. 56.0kg, imageRUNNER 2520: Approx. 50.5kg
PRINT SPECIFICATION		
PDL		UFRII-LT, PCL5e/6 (standard on i models, optional on non i models), PostScript level 3 emulation (optional)
Resolution		600 x 600dpi, 1200dpi x 1200dpi (UFRII-LT only)
Memory		512MB (imageRUNNER 2500 i models), 256MB (imageRUNNER 2500 non i models)
Hard Disk		None
CPU		Canon Custom Processor, 400MHz
Fonts		PS Fonts: Roman 136, PCL Fonts: Roman 93
Supported OS		PCL: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7 Postscript level 3 emulation: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Mac OS X (10.4 or later) UFRII-LT: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7, Mac OS X (10.4 or later), Linux Mac-PPD: Mac OS X 10.4 or later
Interface		Ethernet (100Base-TX / 10Base-T)
Network Protocol		TCP / IP (LPD / Port9100, HTTP), SMB, SNMPv1, WSD, IPv4 / IPv6 support
Pull Scan		Network TWAIN Driver (75 / 100 / 150 / 200 / 300dpi 8bit colour / 75-600dpi 1bit Black-and-White)
SEND SPECIFICATION/ CLR SEND KIT-Y1 (standard on i models, optional on non i models)		
Scan Speed (A4, 300dpi, BW/Colour)		45 / 34ipm (45 / 35ppm model), 25 / 13ipm (30 / 25 / 20ppm model)
Scan Resolution	BW	100 x 100dpi, 150 x 150dpi, 200 x 100dpi, 200 x 200dpi, 200 x 400dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi
	CL	100 x 100dpi,150 x 150dpi, 200 x 200dpi, 300 x 300dpi
Destinations		E-Mail / Internet FAX (SMTP), PC / Server (SMB,FTP), iWDM USB memory keys
Address Book		Local (Max. 500)
File Format		TIFF, JPEG, PDF, High compression PDF, Searchable PDF (optional with Searchable PDF-C1)

DADF-AA1 for imageRUNNER 2545/2535		
Paper Size		A3, A4, A4R, A5, A5R
Paper Weight		Single sided original: 42 to 128g/m², Double sided original: 50 to 128g/m²
Max. Number of Originals		100 sheets (A4, A4R, A5, A5R: 80g/m²), 50 sheets (A3: 80g/m²)
Document Scanning Speed (max.)	Copy	45ipm (A4, 600 x 600dpi: BW)
	Scan	45 / 34ipm (A4, 600 x 600dpi: BW / 300 x 300dpi: Colour)
Dimensions (W x D x H)		565 x 540 x 137mm
Weight		Approx. 7.9kg
DADF-AB1 for imageRUNNER 2530/2525/2520		
Paper Size		A3, A4, A4R, A5, A5R
Paper Weight		Single sided original: 37 to 128g/m², Double sided original: 50 to 128g/m²
Max. Number of Originals		50 sheets (A4, A4R, A5, A5R: 80g/m²), 25 sheets (A3: 80g/m²)
Document Scanning Speed (max.)	Copy	25ipm (A4, 600 x 600dpi: BW)
	Scan	25 / 13ipm (A4, 600 x 600dpi: BW / 300 x 300dpi: Colour)
Dimensions (W x D x H)		565 x 544 x 126mm
Weight		Approx. 7.0kg
CASSETTE UNIT-W1 for imageRUNNER 2520/i		
Type		Front-loading adjustable drawers
Paper Size		A3, A4, A4R, A5R
Custom Size		139.7 to 297mm x 182 to 432mm
Paper Weight		64 to 90g/m²
Paper Capacity		550 sheets (80g/m²) x 1 cassette
Dimensions (W x D x H)		565 x 680 x 97mm
Weight		Approx. 12.8kg
CST. FEEDING UNIT-AE1 for all models		
Type		2 Front-loading adjustable drawers
Paper Size		A3, A4, A4R, A5R
Custom Size		139.7 to 297mm x 182 to 432mm
Paper Weight		64 to 90g/m²
Paper Capacity		550 sheets (80g/m²) x 2 cassettes
Dimensions (W x D x H)		565 x 680 x 248mm
Weight		Approx. 24.0kg
INNER FINISHER-B1 for all models		
Number of Trays		One stack tray (Optional 2nd Tray; INNER FIN ADD. TRAY-B1)
Tray Capacity		A4, A5, A5R: 1,000 sheets (or 125mm in height) A3, A4R: 500 sheets (or 62.5mm in height)
Staple Position		Corner, Double
Staple Capacity		A4: 50 sheets x 30 sets; A4R / A3: 30 sheets x 15 sets
Dimensions (W x D x H)		416 x 554 x 350mm, 703 x 554 x 350mm (with output tray extended)
Weight		Approx.12.5kg
INNER 2-WAY TRAY-G1 for all models		
Number of Trays		2 stack tray
Tray Capacity	Tray A	A4: 250 sheets, A3: 100 sheets
	Tray B	A4: 100 sheets, A3: 50 sheets
Dimensions (W x D x H)		426 x 413 x 109mm
Weight		Approx. 0.6kg
OTHER ACCESSORIES		Platen Cover Type P: for imageRUNNER 2525/2530 without DADF Platen Cover Type Q: for imageRUNNER 2535/2545 without DADF Stamp Ink Cartridge-C1 Stamp Unit-B ADF Access Handle-A1 PCL Printer Kit-AF1: Supports PCL5e and PCL6 printing for non-i Models PS Printer Kit-AF1: Supports PostScript Level 3 Emulation printing Barcode Printing Kit-B1: Provides Barcode printing capability using Jet Caps technology Super G3 Fax Board-AG1: Add fax functionality FL Cassette-AJ1: This spare 550-sheet tray for cassette '1' of imageRUNNER 2525 / 2525i / 2530 / 3530i / 2535 / 2535i / 2545 / 2545i FL Cassette-AK1: This spare 550-sheet tray for cassette '2' of imageRUNNER 2525 / 2525i / 2530 / 3530i / 2535 / 2535i / 2545 / 2545i or for Cassette Feeding Unit-AE1 or Cassette Module-W1 FL Cassette-AL1: This spare 250-sheet tray for cassette '1' of imageRUNNER 2520 / 2520i allows you to swap paper sizes without changing the printer settings Cassette Spacer-A1: Adjusts the height for 250-sheet cassette when combined with optional Cassette Feeding Unit-AE1 or Cassette Module-W1 on imageRUNNER 2520 / 2520i only Envelope Feeder Attachment-D1: Attaches to cassette '2' for easy envelope feeding imageRUNNER 2500 Plain Pedestal 2 Way Unit-B1: Enhances the double-sided print productivity up to 100% Reversal Pass Unit (2-Way Unit) option for imageRUNNER 2520 / 2520i / 2525 / 2530 Staple-J1: Staples for Inner Finisher-B1 Document Tray-J1: Handy tray that attaches to the side of the device Power Supply Unit-U1 Card Reader Attachment-D3: Attachment kit for Card Reader-E Canon Card Reader-E1: Physical card access system that limits system access to authorised users USB Application 3-Port Interface Kit-A1: 3-Port USB interface kit for USB memory CCVI I/F Cable-A1: Interface Kit for Coin-Vender C-EXV33 TONER BK: Toner for imageRUNNER 2520 / 2520i / 2525 / 2525i / 2530 / 2530i C-EXV32 TONER BK: Toner for imageRUNNER 2535 / 2535i / 2545 / 2545i

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.
www.canon.com

Canon Europa
www.canon-europe.com

English Edition 0142W790
© Canon Europa 2009 (0210)